

**ebm-papst St. Georgen GmbH & Co. KG**

Hermann-Papst-Str. 1

D-78112 St. Georgen

Phone +49 (0) 7724 81-0

info2@de.ebmpapst.com

www.ebmpapst.com

Nominal data

Item	8830 N	
Motor	-0	
Phase		1~
Nominal voltage	VAC	115
Frequency	Hz	60
Speed (rpm)	min ⁻¹	1950
Power consumption	W	8.0
Min. ambient temperature	°C	-10
Max. ambient temperature	°C	80
Air flow	m ³ /h	36
Sound power level	B	3.7
Sound pressure level	dB(A)	21

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Technical description

Weight	0.490 kg
Dimensions	80 x 80 x 38 mm
Impeller material	Sheet steel, painted black
Housing material	Die-cast aluminum
Airflow direction	Exhaust over struts
Service life L10 at 40 °C	62500 h
Service life L10 at maximum temperature	25000 h

AC axial panel compact fan

Technical drawing of the cooling unit assembly showing dimensions and tolerances:

- Top edge dimensions: $38^{+0,3}$ and $3^{+0,2}$
- Left side dimensions: 310^{+10} and 6^{+1}
- Bottom edge dimensions: $71,5^{+0,2}$, $79,5^{+0,3}$, and $4,3^{+0,15}$
- Right side dimensions: $71,5^{+0,2}$ and 77
- Internal dimensions: $4,5^{+0,2}$ and $4,3^{+0,15}$
- Central hole diameter: $\varnothing 90$

Curves: Air performance

