



H3CR-A 100-240VAC/100-125VDC

Timer, plug-in, 11-pin, DIN 48 x 48 mm, multifunction, 0.05 s-300 h, DPDT, 5 A, 100 to 240 VAC, 100-125VDC

Type	Analog
Installation type	DIN rail, On-panel, Socket
Functions	Multi-functional
Size	1/16 DIN (48 x 48 mm)
Terminal type	Plug-in
Operating mode	Flicker OFF Start (Signal Start), Flicker ON Start (Signal Start), Interval (Signal Start), OFF Delay (Signal), ON Delay (Signal Start), One-shot Output (Signal Start), Signal ON/OFF Delay
Output type	Relay
Contact description	DPDT
Time range	0.05 s - 300 h
Supply voltage AC	100-240 V
Supply voltage DC	100-125 V
Number of pin contact	11
Inputs	No-voltage

Aksesuarlar



P3GA-11

Socket, back-connecting, 11-pin, screw terminals



Y92A-48B(H.FRONTCOVER FOR H3BA)

Protective cover for DIN 48x48 mm device, hard plastic



Y92F-30

Flush panel mounting adapter for DIN 48x48 mm device



Y92F-73

Adapter for H3CR replacement of STP-YMH timer



Y92P-48GL

Panel cover for H3CR-A* timer, light grey

İlgili ürünler



P2CF

P2CF; H3CA/R ve H5CN/X/Z Zaman Röleleri ile H7CC/N/X/Z Sayaçlar için soket serisidir

CAD dosyası



H3CR-AI-F/-G/-H Solid-state Timer Veri Sayfası

EN PDF 7,51 MB



Timers Broşür

EN PDF 9,85 MB